# **CWC Premium Series**

## Cold Water - Gasoline - Belt Drive

#### Pump:

- External bypass system allows more water into the system to protect from heat build-up
- Forged brass manifold
- Thermal and safety relief valves
- Water filter with clear sleeve for screen inspection (High capacity water filter on CWC-3008-4MGH)

#### Frame:

- Powder coated steel frame with 1<sup>1</sup>/<sub>4</sub>-inch roll cage, handles and lifting hook
- Convenient gun/wand holder and hose wrap
- Two-piece belt guard for quick access to belts
- 13-inch flat-free tires with locking tire brake

#### Components:

- Fuel tank has powder coated outside and aluminized steel inside to prevent rusting
- 13-gallon fuel tank capacity for 9½ hour run time
  Unit Includes:
- Quick connect nozzles 0°, 15°, 25° and 40°
- 50-foot x <sup>3</sup>/<sub>4</sub>-inch high pressure hose with quick connects (CWC-5000 models have a non-marking hose; CWC-6004 and CWC-7004 models have a black hose)
- 50-foot x ½-inch high pressure black hose with quick connects (CWC-3008-4MGH)
- Professional-grade insulated trigger gun with safety lock-off

### Limited Warranties:

3 year Honda engine7 year AR and General pumps

#### Certification:

 Intertek - Certified to UL-1776 (CWC-5004-4MAH, CWC-5004-4MGH and CWC-5005-4MGH)



One of the most durable cold water pressure washers on the market today, the CWC Premium Series is equipped with a durable roll cage. It is perfect for industrial jobsites where heavy-duty cleaning is needed.

| MODEL NUMBER  | PSI  | GPM | DISPLACEMENT/ENGINE                                      | PUMP    | Mi-T-M NO. | UNLOADER       | LANCE | DIMENSIONS (LxWxH)  | SHIP WT. | NET WT. |
|---------------|------|-----|--|---------|------------|----------------|-------|---------------------|----------|---------|
| CWC-3008-4MGH | 3000 | 8.0 | 688cc Honda GX630 OHV, electric start - battery included | General | 3-0279     | Factory preset | 48in. | 43x27.75x36in.      | 531 lb.  | 408 lb. |
| CWC-5004-4MAH | 5000 | 4.0 | 688cc Honda GX630 OHV, electric start - battery included | AR      | 3-0213     | Factory preset | 48in. | 43x27.75x36in.      | 521 lb.  | 398 lb. |
| CWC-5004-4MGH | 5000 | 4.0 | 688cc Honda GX630 OHV, electric start - battery included | General | 3-0261     | Factory preset | 48in. | 43x27.75x36in.      | 521 lb.  | 398 lb. |
| CWC-5005-4MGH | 5000 | 5.0 | 688cc Honda GX630 OHV, electric start - battery included | General | 3-0262     | Factory preset | 48in. | 43x27.75x36in.      | 531 lb.  | 408 lb. |
| CWC-6004-4MGH | 6000 | 3.7 | 688cc Honda GX630 OHV, electric start - battery included | General | 3-0261     | Factory preset | 48in. | 43x27.75x36in.      | 531 lb.  | 408 lb. |
| CWC-7004-4MGH | 7000 | 3.8 | 688cc Honda GX690 OHV, electric start - battery included | General | 3-0430     | Factory preset | 48in. | 43.25x28.5x39.25in. | 521 lb.  | 398 lb. |

#### Accessories:

| PART NUMBER | DESCRIPTION                         | FITS MODELS                   | PART NUMBER  | DESCRIPTION                         | FITS MODELS                |
|-------------|-------------------------------------|-------------------------------|--------------|-------------------------------------|----------------------------|
| 851-0089    | 50-ft. x 1/2-in. high pressure hose | CWC-3008-4MGH                 | 851-0420     | 50-ft. x 3/8-in. high pressure hose | CWC-7004-4MGH              |
| 851-0317    | 50-ft. x 3/8-in. non-marking hose   | CWC-5004, CWC-5005 & CWC-6004 | AW-0018-0375 | Rotating nozzle                     | CWC-7004-4MGH              |
|             |                                     | models                        | AW-7500-0035 | Rotating nozzle                     | CWC-5004 & CWC-6004 models |