

1300 232 456

e: b.meredith@cleanquip.com.au

www.cleanquip.com.au

SC UNO 7P 180/1200

PART NUMBER 107340510

Stationary single pump high pressure cleaners for flexible cleaning
The SC UNO range of industrial stationary cold high pressure cleaners features innovative steps to meet specific cleaning needs and heavy-duty cleaning challenges with convincing performance.

These machines offer a variety of configurations according to user situations – at an attractive price level. Furthermore, intuitive user functions and the opportunity to customise the machines with equipment suited for your environment ensure high productivity.


The ideal and powerful choice

The SC UNO series introduce a new innovative hard foam cabinet, meeting specific hygienic demands, e.g. within the food industry, and the foam material also reduces the noise level. Together with the new simple control panel, it makes all models ideal for agriculture with milking sheds, sties, and stables. For food and pharma industry with processing equipment, conveyors, and tanks. For shipping and industry with ship decks, bulkheads, and industrial equipment. In rental, retail, trade, building and construction, car wash areas, etc. Even oil and grease can be removed thanks to the hot water inlet and high-pressure detergent injector. Low pump oil warning lamp, service warning lamp and hour counter is standard.

Customise for your environment

Choose a basic or more feature packed model to meet your specific needs Extra features; full stainless steel frame; high-pressure detergent injector; coin box, water brake tank, accessory storage kit Dry run/low water safety and inlet water safety kit. Further customization: Can be configured with PCB electronic controls enabling optional equipment such as remote control, coin boxes, and frost protection. Optional add-ons to fulfill EU norm 1717: Water break tank and BA valve.

- NA6 and C3 high-quality industrial motor pumps with brass pump heads
- 4 full ceramic pistons and double roller bearings
- The industrial pumps make it possible to feed the units with hot inlet water from 70°C (with break tank) to 85°C (direct feed) for maximum cleaning efficiency
- Powered by 1450 rpm closed industrial motor
- NA5.2 reinforced wobble disc pump
- Accessory kit included for immediate plug and play use
- Low pump oil safety function and warning lamp
- Hour counter and service warning lamp
- NEO control system, enabling optional functions: remote control, low water safety etc.
- One year commercial warranty



SPECIFICATIONS

Pump Pressure bar/psi 180/2610
Cleaning Impact kg/force 5.9
Water Flow QMAX/QIEC L/min 20-18
Maximum Inlet Temperature Degrees Celcius 80
Pump RPM 1450
Dimensions mm (LxWxH) 355x860x560
Weight kg 81
Power Consumption kW 6.7
Input V~/Hz/A 400/3/50/12.0
Power Cable Length m 5
Pistons Quantity 4 Ceramic
Suction Height - dry m 1
Suction Height - primed m 2.5
Nozzle size in .0640